



<b>5.56</b> CALIBER		<b>55<sup>GR</sup></b> BULLET WEIGHT	<b>FMJBT</b> FULL METAL JACKET BOAT TAIL	<b>20</b> ROUNDS
<b>Dimensions and weight</b>	Max Overall Length	2.259 in		
		57.4 mm		
	Bullet Length	0.760 in		
		19.3 mm		
	Max Case Length	1.758 in		
		44.7 mm		
	Bullet Weight	<b>55 gr</b>		
	Total Round Weight	11.3 g - 11.9 g		
<b>Characteristics (MIL-C-70508 &amp; STANAG 4090 where applicable)</b>	Average Velocity (200MM Proof Barrel @ 15ft)	3050 +/- 50		
	Max Case Mouth Pressure (K2519A)	≤2894 bar / 42000 psi		
	Action Time	≤3		
	Muzzle Energy	1540 J		
	Bullet Extraction Force	200+ Nm		
	Case and Primer Sealant	Hernon Sealant		
		Submerged Vacuum Tested		
	Suggested Operating Temperature	+54 °C / +129 °F to -54 °C / -65 °F		
	Suggested Storage Temperature	+35 °C / +95 °F to -15 °C / +5 °F		
<b>Cartridge Composition</b>	Projectile Jacket	Copper (CuZn10)		
	Projectile Core	Lead Antimony		
	Case Material	Brass (CuZn30)		
	Primer	Boxer Small Rifle, Non-Corrosive		
<b>Powder Charge</b>	Powder Type	Ball Double Base		
	Max Powder Charge	24.4 gr to 24.6 gr Lot Dependent		

Sales Associate:

Date:

Price:

**\*\*This sales sheet contains confidential and proprietary information and is intended solely for the recipient; upon receiving, you agree not to disclose, distribute, or reproduce any part of its contents without prior written consent.\*\***

